



Imperial Productions®
IPTOW16

Top Diameter 30-1/2" (77.4cm)



Ridge 16" Hole 15"

Dimensions

Top Diameter 30-1/2"

Height 28" (71cm)

Inside Hole 15"

Fits Top Shaft to 16"

Materials

ArchPolymer™

an artificial wood primed white easy to install with the approved adhesive and a brad nailer. Finish joining edges with poly spackling compound. Optional Class A fire rating available. Exterior & Interior use

GRG-NeoPlaster™

Much stronger than traditional plaster Class A fire rated product. Screw & glue into place. Priming by others. Interior use.

* All prices & specifications subject to change without notice, Final products & Measurements may vary from this brochure



Imperial Productions®

1-800-399-7585

Imperial Productions & Distribution Inc.

email sales@imperialproductions.com copyright 2016 MRDCI All Rights Reserved

DEC-24



Custom Request (Download & Fill-in)

emailto sales@imperialproductions.com

IPMED500

Name _____

Contact: _____

Phone # _____

Email: _____

Address _____

ZIP/PC _____



MATERIAL SELECTION

Hardwoods: Maple / Red Oak / Alder / Cherry Class B fire rated (Interior)

of Units _____ Wood Species _____

ArchPolymer™ A synthetic Plaster, White Primed Ready to Paint (Interior/Exterior)

of Units _____ for Residential

of FireRated Units _____ for Commercial

GRG-NeoPlaster™ A new age plaster, Class A fire rated (Interior)

of Units _____

ResinMold® A Synaptic polymer for Curves & Arches, Class A fire rated

See Next Page

VALUE ADDED FINISHES

Factory Paint Color Code _____ Finish _____

Metal Coated: Type: _____

* Possible Limitations due to Quantity Requested and/or Application



Imperial Productions®

1-800-399-7585

Imperial Productions & Distribution Inc.

email sales@imperialproductions.com copyright 2016 MRDCI All Rights Reserved